



*Shake water off a duck's back!*

# PCT®

## Treatment for Wood

**SHEDS WATER PERMANENTLY**

**Apply to Aged wood**



**TREATMENT TO CREATE  
WATER REPELLENT  
PROPERTIES**

Economical  
Ready to use  
High solid content  
Flexible  
Contains no toxic solvents  
Acid and alkali Resistant  
UV stable  
Durable

DATA SHEET D-002  
SAFETY DATA SHEET S-002

### SURFACE PREPARATION

Remove all loose and flaking paint.  
Remove all dust, dirt and foreign debris.  
Ensure the surface is dry

### APPLICATION PROCEDURE

Ensure that the surrounding area is protected from overspray.  
Ensure that glazing and aluminium is protected from overspray.  
Apply by means of pesticide spray applicator, 5 liter pressurised applicator or agriculture backpack applicator.  
Ensure that the surface is saturated but avoid the occurrence of damming on the surface.  
When damming occurs, remove excess liquid immediately with a moist cloth.  
Leave for 24 hours for full cure.  
Slightly abrade the surface with 80 grit sandpaper to provide a key for varnish.  
In the event of spillages, neutralise immediately with household vinegar and remove with moist cloth.

### SAFETY HAZARDS

- Do not consume.
- Use a barrier cream on hands.
- Wear surgical gloves during application.
- Wear safety glasses during application.
- Wear safety clothing with elastic tie-down sleeves.
- Do not dispose of into sewers.
- Avoid spillages or overspray on glazing.
- **KEEP OUT OF REACH OF CHILDREN.**



MANUFACTURED BY:  
PCT WATER REPELLENT TECHNOLOGY cc  
Unit 4, Bretts Lane  
Duncanville,  
Vereniging  
South Africa  
TELEFAX +27(0)86 663 4056  
MOBILE +27(0)79 900 2234  
E-MAIL attie@pctwaterrepellent.com  
WEB www.pctwaterrepellent.co.za

**5 Litre  
D-002**